



## Product Data Sheet

Sodíková výbojka

# HPS-T 70W E27 NBB SUPER/4Y

Order number

**746321000**

Unit EAN13 code

**8595209923462**


### General information

|  |                                     |
|--|-------------------------------------|
| Model/Description                              | <b>Sodíková výbojka/Sodium lamp</b> |
| Finish   | <b>Vysokotlaká/HID</b>              |
| Brand/Manufacturer                             | <b>NBB</b>                          |
| Material                                       | <b>Hard Glass</b>                   |
| Nominal service life (h)                       | <b>32000 h</b>                      |
| Model  | <b>Čirá</b>                         |
| Socket   | <b>E27</b>                          |
| Dimmable                                       | <b>Ano</b>                          |
| Energy efficiency class (canceled regulation!) | <b>A+</b>                           |
| Dimmable by conventional dimmers               | <b>Ne</b>                           |
| Název položky                                  | <b>HPS-T 70W E27 NBB SUPER/4Y</b>   |
| Třída energetické účinnosti podle 2019/2015    | <b>F</b>                            |

### Electrical characteristics

|                                 |               |
|---------------------------------|---------------|
| Nominal wattage                 | <b>70 W</b>   |
| Rated power (W)                 | <b>70,0 W</b> |
| Operating voltage (V)           | <b>90 V</b>   |
| Type of Voltage                 | <b>AC</b>     |
| Pulse height                    | <b>5 kV</b>   |
| Direct connection to the mains  | <b>Ne</b>     |
| Lamp power                      | <b>70 W</b>   |
| Nominal current (A)             | <b>0,98 A</b> |
| Total power (W) (light fitting) | <b>70 W</b>   |

### Working conditions

|                                     |                   |
|-------------------------------------|-------------------|
| Hot restart                         | Ano               |
| Bulb temperature (max.)             | 310 °C            |
| Cap temperature (max.)              | 210 °C            |
| Burning position                    | Libovolná         |
| Typical Hot Restart Time            | 5 min             |
| Suitable for domestic use.          | Ne                |
| Application                         | Veřejné osvětlení |
| External ignitor required           | Ano               |
| External ballast required           | Ano               |
| Lighting for plants                 | Ne                |
| Replacement for mercury vapour lamp | Ne                |

#### Mounting methods/application

|                 |                   |
|-----------------|-------------------|
| Mounting method | Uravřená svítidla |
|-----------------|-------------------|

#### Physical characteristics

|                          |                       |
|--------------------------|-----------------------|
| Light centre length (mm) | 101 mm                |
| Dimensions (mm)          | Ø38 x 156 mm          |
| Packing method           | 40 - 1                |
| Weight gross             | 75 g                  |
| Weight netto             | 66 g                  |
| Total lenght             | 156 mm                |
| Diameter                 | 38 mm                 |
| Lamp shape               | Jednopaticová válcová |
| Number of Burners        | 1                     |
| Coated                   | Ne                    |

#### EuP Parameters

|  |              |
|--|--------------|
| Average Lifetime B50 (h)                               | 32000 h      |
| Luminescence Life maintenance factor                   | 73,0 %       |
| Factor of functional reliability (LSF) after nom. life | 70,0 %       |
| Starting time to 90% of the light flow                 | 120 s        |
| The rate of premature failures                         | <1 %         |
| Rated service life                                     | 32000 h      |
| Energy consumption (AGGR)                              | 70 kWh/1000h |
| Turn-on time   | 5 s          |

#### Lighting characteristics

|                            |         |
|----------------------------|---------|
| Dominant wavelength        | 598 nm  |
| Luminous flux              | 6600 lm |
| Colour temperature         | 2000 K  |
| Colour rendering index CRI | 25 Ra   |
| Chromaticity coordinates x | 0,525   |
| Chromaticity coordinates y | 0,430   |
| Vyzařovací úhel            | 330 °   |

#### Safety information

|                     |  |
|---------------------|--|
| Safety instructions | <a href="http://www.nbb.cz">www.nbb.cz</a> |
|---------------------|--|

#### Environmental characteristics

|                 |      |
|-----------------|------|
| Mercury-free    | Ne   |
| Mercury content | 8 mg |

#### Energetic characteristics

|                             |         |
|-----------------------------|---------|
| Rated efficiency after 100h | 99,99 % |
| Lamp efficacy               | 94 lm/W |

#### Lamp survival factor (LSF)

|                      |         |
|----------------------|---------|
| LSF after 100 hrs    | 100,0 % |
| LSF after 2.000 hrs  | 100,0 % |
| LSF after 4.000 hrs  | 100,0 % |
| LSF after 6.000 hrs  | 100,0 % |
| LSF after 8.000 hrs  | 98,0 %  |
| LSF after 10.000 hrs | 98,0 %  |
| LSF after 12.000 hrs | 95,0 %  |
| LSF after 16.000 hrs | 92,0 %  |
| LSF after 20.000 hrs | 89,0 %  |
| LSF after 25.000h    | 80,0 %  |
| LSF after 28.000 hrs | 70,0 %  |

#### Lamp lumen maintenance factor (LLMF)

|                       |         |
|-----------------------|---------|
| LLMF after 100 hrs    | 100,0 % |
| LLMF after 2.000 hrs  | 98,0 %  |
| LLMF after 4.000 hrs  | 96,0 %  |
| LLMF after 6.000 hrs  | 94,0 %  |
| LLMF after 8.000 hrs  | 93,0 %  |
| LLMF after 10.000 hrs | 90,0 %  |
| LLMF after 12.000 hrs | 88,0 %  |
| LLMF after 16.000 hrs | 83,0 %  |
| LLMF after 20.000 hrs | 78,0 %  |
| LLMF after 24.000 hrs | 75,0 %  |
| LLMF after 28.000 hrs | 73,0 %  |

#### Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

#### Popis

High pressure sodium lamp SUPER 4Y Long Life (28.000 h), 6.600 lm.

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o Všechna práva vyhrazena.