



## Product Data Sheet

Metal-halogenidová výbojka

**JLS-T 150W/830 UVS**  
**CERA® G12 MINI**

Order number

**741031010**

Unit EAN13 code

**8595209921468**


### General information

Model/Description	<b>Vysokotlaká výbojka</b>
Finish	<b>Křemíková/Quartz</b>
Brand/Manufacturer	<b>NBB</b>
Bulb finish	<b>clear</b>
Material	<b>Hard Glass</b>
Nominal service life (h)	<b>10000 h</b>
Model	<b>Čirá</b>
Socket	<b>G12</b>
Dimmable	<b>Ano</b>
Energy efficiency class (canceled regulation!)	<b>A</b>
Lamp voltage	<b>90 - 95 V</b>
Dimmable by conventional dimmers	<b>Ne</b>
Název položky	<b>JLS-T 150W/830 UVS CERA® G12 MINI</b>

### Electrical characteristics

Nominal wattage	<b>150 W</b>
Rated power (W)	<b>150,0 W</b>
Compatible ballast	<b>1,8-2,0 A</b>
Operating voltage (V)	<b>95 V</b>
Type of Voltage	<b>AC</b>
Pulse height	<b>5 kV</b>
Lamp operating current	<b>1,80 A</b>
Direct connection to the mains	<b>Ne</b>
Lamp power	<b>150 W</b>
Nominal current (A)	<b>1,80 A</b>

## Working conditions

Ambiente temperature for max. luminous flux	max 180s/25°C °C
Hot restart	Ne
Bulb temperature (max.)	500 °C
Cap temperature (max.)	300 °C
Burning position	Libovolná
Application	Pro uzavřená svítidla
Burning position	Libovolná
External ignitor required	Ano
External ballast required	Ano
Material discharge tube	Quartz
Closed luminaire required	Ano

## Mounting methods/application

Mounting method	Uzavřená svítidla
-----------------	-------------------

## Physical characteristics

Dimensions (mm)	Ø25 x 84 mm
Packing method	10 - 1
Weight gross	38 g
Weight netto	30 g
Total lenght	84 mm
Diameter	25 mm
Lamp shape	Jednopaticová válcová
Coated	Ne

## EuP Parameters

Average Lifetime B50 (h)	10000 h
The rate of premature failures	<1 %
Rated service life	10000 h
Energy consumption (AGGR)	165 kWh/1000h
Turn-on time	max 30 s

## Lighting characteristics

Lenght of arc	4,8 mm
Color rendering	1B
Light Colour	teplá bílá
Dominant wavelength	412 nm
Luminous flux	13000 lm
Colour temperature	3000 K
Colour rendering index CRI	85 Ra
Sun tanning lamp	Ne
Colour of light	830
Colour of light acc. EN 12464-1	Warm <3300 K
Chromaticity coordinates x	0,443
Chromaticity coordinates y	0,409

## Radiation in the UV range

UV protect	Ano
------------	-----

## Safety information

Safety instructions	<a href="http://www.nbb.cz">www.nbb.cz</a>
---------------------	--

## Environmental characteristics

Maximum mercury content (mg)	max 4,00 mg
------------------------------	-------------

## Energetic characteristics

Rated efficiency after 100h	99,8 %
Lamp efficacy	86,66 lm/W

## Lamp survival factor (LSF)

LSF after 2.000 hrs	90,0 %
LSF after 4.000 hrs	75,0 %
LSF after 6.000 hrs	50,0 %
LSF after 8.000 hrs	90 %
LSF after 9.000 hrs	80 %
LSF after 10.000 hrs	50 %
LSF after 12.000 hrs	50 %

## Lamp lumen maintenance factor (LLMF)

LLMF after 2.000 hrs	80,0 %
LLMF after 4.000 hrs	60,0 %
LLMF after 5.000 hrs	60 %
LLMF after 6.000 hrs	60,0 %
LLMF after 10.000 hrs	50 %
LLMF after 12.000 hrs	40 %

## Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

## Popis

Ceramic metal-halide lamps MINI, 10.000 h, Ra 80+, UV-stop, 13.000 lm, 3000 K, only for enclosed fixture

**NBB Bohemia s.r.o., Sídliště 693, 407 22 Benešov nad Ploučnicí**  
<https://www.nbb.cz/en/> | [hotmail@nbb.cz](mailto:hotmail@nbb.cz)

Copyright CE 2024 NBB Bohemia s.r.o. Všechna práva vyhrazena.