



Product Data Sheet

LED žárovka (oranžová)

LED A60 230-240V 2W
COLOURMAX E27
ORANGE



Order number

250656050

Unit EAN13 code

8595209943705

General information

Model/Description	Světelný zdroj LED
Brand/Manufacturer	NBB
Material	PC
Lamp type	A60
Nominal service life (h)	30000 h
Colour	Oranžová
Socket	E27
Dimmable	Ne
Energy efficiency class (canceled regulation!)	A++
Nominal voltage (V)	230 - 240 V
Degree of protection (IP)	IPX4
Dimmable by conventional dimmers	Ne
Název položky	LED A60 230-240V 1W COLOURMAX E27 ORANŽOVÁ
Třída energetické účinnosti podle 2019/2015	G

Electrical characteristics

Nominal wattage	1,00 W
Rated power (W)	1,00 W
Operating voltage (V)	100 - 277 V
Endurance	265 V
Type of Voltage	AC
Lowest permitted operating voltage (V)	180 V
Nominal current	24 mA
Lamp power	1 W
Voltage type	AC

With remote control	Ne
Total power (W) (light fitting)	1 W

Working conditions

Type of start	Okamžitý start
Integrated driver	Ano
Maximum permitted storage temperature	80 °C
Burning position	Libovolná
Suitable for domestic use.	Ne
Application	Dekorativní účely
Vhodné pro světelné řetězy	Ano
Suitable for frequent switching	Ano
Ambient temperature	-30/+30 °C

Physical characteristics

Type of chip	EPISTAR
Dimensions (mm)	Ø45 x 72 mm
Packing method	100 - 5
Weight gross	22 g
Weight netto	30 g
Diameter	60 mm
Lamp shape	Standard
Length	107 mm
Number of LEDs	4

EuP Parameters

Average Lifetime B50 (h)	25000 h
Luminescence Life maintenance factor	80,0 %
Factor of functional reliability (LSF) after nom. life	50,0 %
Number of maximal switching cycles	100000
The rate of premature failures	<0,1 %
Colour difference	90 %
Rated service life	25000 h
Energy consumption (AGGR)	1 kWh/1000h
Survival Factor	70
GLS replacement	32 W

Lighting characteristics

Light Colour	oranžová
Dominant wavelength	607 nm
Luminous flux	60 lm
Colour temperature	1367 K
Colour rendering index CRI	70 Ra
Maximal intensity (Cd)	6 Cd
Colour of light	013
Colour controllable (RGB)	Ne
Beam angle Degrees (°)	330 °
Chromaticity coordinates x	600

Chromaticity coordinates y	370
----------------------------	-----

Safety information

Safety instructions	www.nbb.cz
---------------------	--------------------------------------------

Environmental characteristics

Mercury content	0,00 mg
-----------------	---------

Energetic characteristics

Lamp Power factor (PF)	0,56
Rated efficiency after 100h	99,9 %
Lamp efficacy	70 lm/W
Lamp displacement factor (DF)	0,90

Exclusion of liability

Changes to data are subject to prior notice. NBB Bohemia s.r.o. accepts no responsibility for damages caused by inaccurate interpretation of the content on this site.

Notice

Under the scope of Act 185/2001 Coll. as amended, this product is included in waste group 5 (light sources and luminaires). In view of the harmful effects of mercury on the environment and on human health, the creators of group 5 waste (consumers) are obliged to dispose of used light sources for recycling. Do not throw this product into mixed waste after use. Take it to the nearest store, collection yard, or other designated location for free recycling. You can also dispose of the used products for recycling in our sales outlets or in collection points of collective recycling systems or municipal collection yards. Ecological recycling of waste electrical and electronic equipment is ensured through the RETELA collective system (www.retela.cz).

Notice

Single LED chip failure, luminous flux deviation +/- 10% as well as chromaticity deviation +/- 150K are in compliance with applicable standards and are not a reason for complaint.

Popis

Technical drawing



